

AIR FORCE RESEARCH LABORATORY

Uninhabited Systems and Operator Control

John Reising

**Human Effectiveness Directorate
Warfighter Interface Division
Wright-Patterson AFB OH 45433-7022**

December 2005

Approved for public release;
Distribution is unlimited.

**Human Effectiveness Directorate
Warfighter Interface Division
Wright-Patterson AFB OH 45433**

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) Dec-2005		2. REPORT TYPE Technical Paper		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Uninhabited Systems and Operator Control				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) John Reising				5d. PROJECT NUMBER 7184	
				5e. TASK NUMBER 00	
				5f. WORK UNIT NUMBER 00	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Materiel Command Air Force Research Laboratory Human Effectiveness Directorate Wright-Patterson AFB OH 45433-7022				8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-HE-WP-TP-2005-0034	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Materiel Command Air Force Research Laboratory Human Effectiveness Directorate Warfighter Interface Division Wright-Patterson AFB OH 45433-7022				10. SPONSOR/MONITOR'S ACRONYM(S) AFRL/HEC	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES These are briefing charts. Clearance: AFRL/WS-05-2090, 4 Oct 05.					
14. ABSTRACT This was a briefing presented to the UCAV Conference in London UK.					
15. SUBJECT TERMS Uninhabited Systems					
16. SECURITY CLASSIFICATION OF: Unclassified			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 43	19a. NAME OF RESPONSIBLE PERSON John Reising
a. REPORT UNC	b. ABSTRACT UNC	c. THIS PAGE UNC			19b. TELEPHONE NUMBER (include area code) (937) 255-255-8869

AFMC/PA



Air Force Research Laboratory Human Effectiveness Directorate



Dr. John M. Reising
Technical Adviser
Warfighter Interface Division


Uninhabited Systems and Operator Control

Voice: 937-255-8769
 Fax: 937-255-7596
 Email: john.reising@wpafb.af.mil
 www.hec.afrl.af.mil
 AFRL-WS-05-0408 18 Feb 2005





DEPARTMENT OF THE AIR FORCE
 SAF/PAX
 OCT 4 2005
 CLEARED THIS INFORMATION
 FOR PUBLIC RELEASE

1



Human and Machine Co-operate





Meet
Human Factors.

This is a
SAF/PAX doc

05-0477

Call 697-0422 or 697-6715
 For pickup or return to
 4A120

AFMC 05-342

AFRL/WS 05-2090



Human-electronic Crewmember Conferences




THE HUMAN-ELECTRONIC CREW: CAN THEY WORK TOGETHER ?
Conference Room at Stadttheater Ingolstadt
Ingolstadt, FRG, 19 - 22 Sept 1988



**THE HUMAN - ELECTRONIC CREW:
IS THE TEAM MATURING?**

The 2nd Joint GAF/RAF/USAF Workshop
on Human - Electronic Crew Teamwork
Stadttheater Conference Room, Ingolstadt, FRG
25-28 September 1990



**THE HUMAN-ELECTRONIC CREW:
CAN WE TRUST THE TEAM?**
Proceedings of the 3rd International Workshop on
Human-Computer Teamwork
Cambridge, United Kingdom, 27-30 September 1994



**THE HUMAN-ELECTRONIC CREW:
THE RIGHT STUFF?**

Proceedings of the 4th Joint GAF/RAF/USAF
Workshop on Human-Computer Teamwork
Hotel zur Post, Kreuth, Nr Tegernsee, Germany
23 - 26 September, 1997



THREE PILAS OF SUPPORT



Application Areas for Unmanned Vehicles



UAV's


UGV's

UUV's





Air, Ground, and Undersea Examples



Source: Unmanned Systems Volume 16 No. 4 • 6, 2000

0107501RefiningREV




Supervisory Control



“ Specifically, supervisory control means that human **operators plan and teach** tasks to computers, and the **computers then implement** the tasks automatically through their own sensory inputs, memory and control actions”



Personal Satellite Assistant




Personal Satellite Assistant Application






Robonaut



Current USAF UAVs





Predator and Ground Control Stations



Predator Ground Control Station

<http://www.ga.com/asi/photolib/photolib.html>




Tactical Control Station



<http://home.navy.mil/tos/images/images.html>



Dragon Eye




http://www.beyond2000.com/news/May_01/story_1134.html





Interface Technologies



Rationale for Speech Input in UAV Control Stations



- Natural and intuitive interface
- Mature technology
 - Real-time
 - Accurate
 - Speaker-independent
- Reduces resource competition
- Hands-free control
- Heads-up control
- “Voice macros” can replace complex series of manual inputs



Speech input improved performance in manned aircrew applications



Speech Input Implementation




- Speech Recognizer:
 - Nuance v8.0
 - continuous, speaker-independent
- Vocabulary:
 - 70 commands
 - Total vocabulary: 160
- Push-to-Talk button (on joystick)
- Sennheiser 280-13 Pro headset/mic
- Visual feedback of commands on HUD
- Auditory environment: benign



17



Results – Speech Better: Mean Task Completion Time




- Speech input significantly faster for all task types
- Average time savings range: 3.14 to 21.43 seconds
- Data entry time reduced by approx 40% with Speech Input



Results – Speech Better: Mean Task Completion Accuracy



Speech Input more Accurate than Manual



- More tasks completed *correctly* with Speech:
Voice macros are a factor
- Time outs less with Speech: Operators more frequently completed trials within the experimenter-specified time limit with Speech Input.

19



Results – Speech Better Subjective Data



OPERATOR RATINGS

- Manual “more difficult” than Speech
- Manual “higher workload” than Speech
- Manual worse than Speech for:
 - Interference with flight/navigation task
 - Speed and accuracy of data entry


OPERATOR COMMENTS

MANUAL: “Menu...unintuitive.” “Info buried too deep.” “Have to be heads down.”

VOICE: “Voice was just so much easier.”
“You can stay heads-up.”
“Greatly reduced workload.”



UCAV




Col Michael Leggett, UCAV Conference, London 2003

21



Operator's Console Example




22





Operator Vehicle Interface Workstations



Situational Awareness Display Format







Mission Control Station Experimental Laboratory



Operator Console Development



Multi-Sensory Interface Technology Progression

UAV Reconnaissance - UCAV SEAD/Strike Effectiveness ↑



Current Technology
160 Inch² CRT Displays
HOTAS
Multi Layer Menus
No Virtual Technology



Multi-Sensory Displays
Visual Symbolology
Information Fusion
Haptic Displays
Spatial Auditory
Predator Application
10% Virtual Technology



Partial Immersion
3-D Multi-Sensory Displays
Synthetic Vision
Tactile Displays
Speech Control
Spatial Audio
Supervisory Control Interface
UAV + UCAV Application
50% Virtual Technology

1999


2003

2005

©2002 Raytheon Corp



Operator-Vehicle System Diagram




29




Human-machine Control Architectures




(a) Manual Control



(b) Supervisory Control



(c) Co-operative Functionings



Key: H= Human M= Machine
PVI= Pilot Vehicle Interface

Taylor 1902 AGARD LS 122

30



Automation Concerns



**ACCIDENTS DIRECT FOCUS
ON COCKPIT AUTOMATION**

DAVID HUGHES/BOSTON and MICHAEL A. DORNHEIM/LOS ANGELES

**DRAMATIC INCIDENTS HIGHLIGHT
MODE PROBLEMS IN COCKPITS**

MICHAEL A. DORNHEIM/LOS ANGELES

**AIRBUS SEEKS TO KEEP PILOT,
NEW TECHNOLOGY IN HARMONY**

PIERRE SPARACOTTO/LOUISE, FRANCE

**INCIDENTS REVEAL
MODE CONFUSION**

DAVID HUGHES/BOSTON

**NTSB: MODE CONFUSION
POSES SAFETY THREAT**

EDWARD K. PHILLIPS/WASHINGTON

**CERTIFICATION OFFICIALS GRAPPLE
WITH FLIGHT DECK COMPLEXITY**

WILLIAM B. SCOTT/COLORADO SPRINGS

**STUDIES HIGHLIGHT
AUTOMATION 'SURPRISES'**

DAVID HUGHES/BOSTON

AW&ST January 30, 1995

31





Human and Machine Co-operate



Meet
Human Factors.







Associate System



- Associate systems are computer-based aiding systems that are intended to operate as an **associate** to the human user. (Geddes, 1997, p.221)
- **A member without full status or privileges.**
(Webster's New World dictionary 1968, p. 89)

Mixed Initiative -- **both** human and decision aid can take action.

Bounded Discretion -- the human is in charge.

Domain Competency-- decision aid has broad competency, but may have less expertise than its human counterpart.

35



Adaptive Automation




In adaptive automation, the **level or mode** of automation or the **number of systems** that are automated can be **modified in real-time**. Furthermore, **both** the human and the machine share control over changes and the state of automation.

36



Operator-Vehicle System Diagram




37




Human-machine Control Architectures




(a) Manual Control



(b) Supervisory Control



(c) Co-operative Functionings



Key: H= Human M= Machine
PVI= Pilot Vehicle Interface

Taylor 1992 AGARD LS 122

38



Level of Automation and Human/System Roles



Level of Automation	Human Role	System Role
1. None	Decide, Act	-----
2. Decision Support	Decide, Act	Suggest
3. Consensual AI	Concur	Decide, Act
4. Monitored AI	Veto	Decide, Act
5. Full Automation	-----	Decide, Act

Endsley, Automation and Situation Awareness, p. 174, 1996.

39




Three Phases of Trust Building



- Early Phase: Based upon the **predictability** of another's behaviors
- Intermediate Phase: Dependability -- "**Summary statistic** of an accumulation of behavioral evidence, which expresses the extent to which another person may be relied upon" (Muir, International Journal of Man-Machine Studies, 1987, 532.)
- Final Stage: **Faith** that a person will be dependable in the **future**.

40



Prime Directives for Associate Systems: Example--Three Laws of Robotics



- A robot *may not harm* a human being, or, through in action, allow a human being to come to harm.
- A robot *must obey the orders* given to it by a human being except where such orders would conflict with the first law.
- A robot *must protect its own existence* as long as such protection does not conflict with the first or second law.




- 43

- Process Intel "real-time" from all available resources
- Gather Intel data to relay to higher echelons

- Reasons on info to assess battlefield situation and aircraft/team members' conditions
- Infer the enemy's intent

- Provides pilot selectable task automation
- Monitor crew actions/reactions to predict information required for situation
- Present info to crew, when needed, in form most easily understood

- Understands commander's intent; infers pilot's intent & plans accordingly
- Presents options for changing battlefield situations & pilot makes decisions
- Plans for Route, Recon, Attack, Com, Survivability, and Sensors



BB-085-0101R



Rotorcraft Pilot's Associate: Real-time Computer-aided Decision Making



- **Understands Commander's Intent;
Infers Pilots Intent and Plans
Accordingly**
- **Presents Options for Changing Battlefield
Situations, and Pilot Makes Decisions**
- **Plans for Route, Recon, Attack, Com,
Survivability, and Sensors**

45




Longbow Apache






Operator-Vehicle System Diagram





47




Workload, Unpredictability and Adaptiveness







Increased Unpredictability




"What is PSA doing now?"





51



Operator-Vehicle System Diagram



52





Plan Generated From GUI Playbook





Figure 9. Finished plan returned by the MAC after User specification of the Ingress task.

Miller, Pelican and Goldman, 1999

55




Operator-Vehicle System Diagram




56



Adaptive Automation System Diagram




UCAV Adaptive Automation








Current Research Program



Closed Loop Adaptive Aiding - OVI UCAV Simulator



Performance Results









Summary




- Affordability will result in a **high degree of automation** in the UMV operator's console.
- Control of the UMV will be defined more in terms of **mission management** than manual control.
- Changes on the battlefield will require a very **flexible automation architecture**.
- Successful **team building** between the operator and the automation will require **trust** between the two.
- The UMV operator/console system is a **key feature** in achieving future mission success.

65



Questions



66


- **Slide 1** Contains four pictures: **A)** Across the top of the slide are the Summary Panels, one for each of the UAVs. The summary panels give the operator a quick view of the status of each of the UAVs. **B)** shows the command window. Two very important features are the yellow and red boxes. They enable the operator to disconnect from the boom after refueling and breakaway if an emergency occurs. **C)** The Fuel System display shows the total quantity and individual fuel tank quantities for the selected UAV. **D)** The refueling status display contains three lights. The lights are blue for ready (RDY), green to show contact with the boom (AR), and yellow to show the boom disconnect (DISC). The total fuel quantity of each UAV is shown below these three lights.
- **Slide 2** shows The Out-the-Window display which was a virtual display depicting the positional information of the UAVs and tanker.
- **Slide 3** shows position information about the UAVs, tanker, commanded positions. It is the primary mechanism for commanding the UAVs during the air refueling process.
- **Slide 4** shows that once the UAVs were positioned at the observation positions, and the UAV operator received permission from the boom operator to move, the operator used the mouse to drag the selected first UAV, Striker 01, to the precontact position.
- **Slide 5** shows that the Striker 01 is now in the contact position.
- **Slide 6** shows that all of the Strikers have been refueled are now in the post refueling position.

Slide 1 **NOTE: Slides printed on both sides**


A



B




C




D




Slide 2



Slide 3



Slide 4



Slide 5



Slide 6

